

SELECTION CHART FOR MODULATING PISTON VALVE

PLEASE COPY THIS PAGE AND FAX IT TO US DULY COMPLETED AT NO. +39 035 531763 TO ALLOW US TO PROCESS YOUR ORDER.

	NOMINAL DIAMETER (DN)	
	15 20 25 32 40 50	7
GENERAL	ACTUATOR SIZE BODY MATERIAL Standard Size BODY MATERIAL Standard Size BODY MATERIAL	
GEN	CONNECTION Valve with bronze body is available only with Gas and Npt connections	THE
	Gas Npt B-w ISO65 ANSI B36.10 B-w ISO 4200 B-w ISO 4200 Clamp ISO 2852 Clamp ASME BPE EN 1092 Flange EN 1092 Flange ANSI	50 31a 1-1/2
	<u>s</u>	
PNEUMATIC POSITIONER	PLUG POOP PROCESS TEMPERATURE FAIL SAFE POSITION FAIL SAFE POSITION FAIL SAFE POSITION PROCESS TEMPERATURE PROCESS TEMPERA	
7	FLUID DN (PIPING) Q	
OTHER INFORMATION	Superheaded steaming	Max m²/h team)
	P1 Min Max (bar) (bar) (bar) P2 Min Max (bar) (bar) (bar) P1 (max min)	P2 (max, min)
	DN in Primas, miny	DN out

Note: Highlighted versions are the standard ones. For special versions please get in touch with M&M to check availability.